

250 - 500 ppm Hydrogen fluoride in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499 Issue date: 4/29/2009 Revision date: 1/6/2023 Version: 5.0

## Warning



	ubstance/mixture and of the company/undertaking
1.1. Product identifier	
SDS no	: 8499
1.2. Relevant identified uses of the substan	nce or mixture and uses advised against
Relevant identified uses Uses advised against	<ul> <li>Industrial and professional uses. Perform risk assessment prior to use.</li> <li>Consumer use.</li> <li>Uses other than those listed above are not supported, contact your supplier for more information on other uses.</li> </ul>
1.3. Details of the supplier of the safety dat	a sheet
Air Liquide UK Ltd Station Road, Coleshill Birmingham, B46 1JY	
1.4. Emergency telephone number	
Emergency telephone number	: 01675 462695 (Available 24/7)
SECTION 2: Hazards identification	
2.1. Classification of the substance or mixt Classification according to Regulation (EC)	
	sure : Compressed gas H280
-	
2.2. Label elements	
Labelling according to Regulation (EC) No. Hazard pictograms (CLP)	
	GHS04
Signal word (CLP) Hazard statements (CLP) Precautionary statements (CLP)	: Warning : H280 - Contains gas under pressure; may explode if heated.
- Storage	: P403 - Store in a well-ventilated place.
2.3. Other hazards	
	Asphyxiant in high concentrations.



250 - 500 ppm Hydrogen fluoride in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Nitrogen	CAS-No.: 7727-37-9 EC-No.: 231-783-9 EC Index-No.: REACH-no: *1	99.95	Press. Gas (Comp.), H280
Hydrogen fluoride	CAS-No.: 7664-39-3 EC-No.: 231-634-8 EC Index-No.: 009-002-00-6 REACH-no: 01-2119458860-33	0.02 - 0.05	Acute Tox. 2 (Oral), H300 Acute Tox. 1 (Dermal), H310 Skin Corr. 1A, H314 Eye Dam. 1, H318 Acute Tox. 2 (Inhalation:gas), H330

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

## SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.	
- Skin contact	: Adverse effects not expected from this product.	
- Eye contact	: Adverse effects not expected from this product.	
- Ingestion	: Ingestion is not considered a potential route of exposure.	
4.2. Most important symptoms and effects, both acute and delayed		

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
- Suitable extinguishing media	: Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire.	
- Unsuitable extinguishing media	: Do not use water jet to extinguish.	
5.2. Special hazards arising from the substance or mixture		
Specific hazards Hazardous combustion products	<ul><li>Exposure to fire may cause containers to rupture/explode.</li><li>None that are more hazardous than the product itself.</li></ul>	



## 250 - 500 ppm Hydrogen fluoride in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

5.3. Advice for firefighters	
Specific methods	<ul> <li>Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.</li> <li>If possible, stop flow of product.</li> <li>Use water spray or fog to knock down fire fumes if possible.</li> <li>Move containers away from the fire area if this can be done without risk.</li> </ul>
Special protective equipment for fire fighters	<ul> <li>In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.</li> <li>Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</li> <li>Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.</li> </ul>

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	<ul> <li>Act in accordance with local emergency plan.</li> <li>Try to stop release.</li> <li>Evacuate area.</li> <li>Ensure adequate air ventilation.</li> <li>Stay upwind.</li> </ul>	
	See section 8 of the SDS for more information on personal protective equipment.	
For emergency responders	: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.	
	Oxygen detectors should be used when asphyxiating gases may be released.	
	See section 5.3 of the SDS for more information.	
6.2. Environmental precautions		
	Try to stop release.	
6.3. Methods and material for containment and cleaning up		
	Ventilate area.	
6.4. Reference to other sections		
	See also sections 8 and 13.	

## SECTION 7: Handling and storage

7.1. Precautions for safe handling	
Safe use of the product	: Do not breathe gas.
	Avoid release of product into atmosphere.
	The product must be handled in accordance with good industrial hygiene and safety procedures.
	Only experienced and properly instructed persons should handle gases under pressure.
	Consider pressure relief device(s) in gas installations.
	Ensure the complete gas system was (or is regularily) checked for leaks before use.
	Do not smoke while handling product.
	Use only properly specified equipment which is suitable for this product, its supply pressure
	and temperature. Contact your gas supplier if in doubt.
	Avoid suck back of water, acid and alkalis.



250 - 500 ppm Hydrogen fluoride in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

Safe handling of the gas receptacle	<ul> <li>Refer to supplier's container handling instructions.</li> <li>Do not allow backfeed into the container.</li> <li>Protect containers from physical damage; do not drag, roll, slide or drop.</li> <li>When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.</li> <li>Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.</li> <li>If user experiences any difficulty operating valve discontinue use and contact supplier.</li> <li>Never attempt to repair or modify container valves or safety relief devices.</li> <li>Damaged valves should be reported immediately to the supplier.</li> <li>Keep container valve outlets clean and free from contaminants particularly oil and water.</li> <li>Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.</li> <li>Close container valve after each use and when empty, even if still connected to equipment.</li> <li>Never attempt to transfer gases from one cylinder/container to another.</li> <li>Never use direct flame or electrical heating devices to raise the pressure of a container.</li> <li>Do not remove or deface labels provided by the supplier for the identification of the content of the container.</li> <li>Suck back of water into the container must be prevented.</li> <li>Open valve slowly to avoid pressure shock.</li> </ul>
7.2. Conditions for safe storage, including any inc	compatibilities         Observe all regulations and local requirements regarding storage of containers.         Containers should not be stored in conditions likely to encourage corrosion.         Container valve guards or caps should be in place.         Containers should be stored in the vertical position and properly secured to prevent them from falling over.         Stored containers should be periodically checked for general condition and leakage.         Keep container below 50°C in a well ventilated place.         Store containers in location free from fire risk and away from sources of heat and ignition.         Keep away from combustible materials.
7.3. Specific end use(s)	None.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Hydrogen fluoride (7664-39-3)	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	2.5 mg/m <sup>3</sup>
Acute - systemic effects, inhalation	2.5 mg/m <sup>3</sup>
Long-term - local effects, inhalation	1.5 mg/m <sup>3</sup>
Long-term - systemic effects, inhalation	1.5 mg/m <sup>3</sup>

Hydrogen fluoride (7664-39-3)	
PNEC: Predicted no effect concentration	
Aqua (freshwater)	0.9 mg/l
Aqua (marine water)	0.9 mg/l
Soil, agricultural	11 mg/kg dwt



## 250 - 500 ppm Hydrogen fluoride in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

Micro-organisms in sewage treatment plant (STP)		51 mg/l
8.2. Exposure controls		
3.2.1. Appropriate engineering controls		
		uate general and local exhaust ventilation. er pressure should be regularily checked for leakages.
	,	sure is below occupational exposure limits (where available).
	•	tors should be used when asphyxiating gases may be released.
	Consider the	use of a work permit system e.g. for maintenance activities.
8.2.2. Individual protection measures, e.g. personal	l protective eq	uipment
	risks related t The following	ment should be conducted and documented in each work area to assess the o the use of the product and to select the PPE that matches the relevant risk. recommendations should be considered: nt to the recommended EN/ISO standards should be selected.
• Eye/face protection :	: Wear safety glasses with side shields.	
Skin protection	Standard EN	166 - Personal eye-protection - specifications.
•	Wear working	gloves when handling gas containers.
	-	388 - Protective gloves against mechanical risk, performance level 1 or higher.
- Other :		shoes while handling containers.
Desciratory analystica		ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection :		ay be used if all surrounding conditions e.g. type and concentration of the s) and duration of use are known.
	Use gas filter	s with full face mask, where exposure limits may be exceeded for a short-term ponnecting or disconnecting containers.
		137 - Self-contained open-circuit compressed air breathing apparatus with full
		not protect against oxygen deficiency.
	Never use an	y kind of filtering respiratory protection equipment when working with this e to it having poor or no warning properties.
	Self contained	d breathing apparatus (SCBA) or positive pressure airline with mask are to be en-deficient atmospheres.
		14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .
Thermal hazards :	None in addit	ion to the above sections.
8.2.3. Environmental exposure controls		
	None necess	ary.

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas.
- Colour	: Mixture contains one or more component(s) which have the following colour(s):
	Gives off white fumes in moist air Colourless.
Odour	: Odour threshold is subjective and inadequate to warn of overexposure.
	Mixture contains one or more component(s) which have the following odour:
	Pungent.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
	It is technically not possible to determine the boiling point or range of this mixture.
	Component with lowest boiling point: Nitrogen -196 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available.
Upper explosion limit	: Not available.
Flash point	: Not applicable for gas mixtures.



250 - 500 ppm Hydrogen fluoride in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

Auto-ignition temperature	: Non flammable.	
Decomposition temperature	: Not applicable.	
pH	: Not applicable for gas mixtures.	
Viscosity, kinematic	: Not applicable.	
Water solubility [20°C]	: Mixture is partially soluble in water	
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.	
Vapour pressure [20°C]	: Not applicable.	
Vapour pressure [50°C]	: Not applicable.	
Density and/or relative density	: Not applicable.	
Relative vapour density (air=1)	: Lighter or similar to air.	
Particle characteristics	: Not applicable.	
9.2. Other information		
9.2.1. Information with regard to physical hazard classes		
Explosive properties	: Not applicable.	
Explosion limits	: Non flammable.	
Oxidising properties	: Not applicable.	

#### 9.2.2. Other safety characteristics

Molar mass	: Not applicable for gas mixtures.
Evaporation rate	: Not applicable for gas mixtures.
Other data	: None.

SECTION 10: Stability and reactivity	
10.1. Reactivity	
	No reactivity hazard other than the effects described in sub-sections below. Data for mixture are not available.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	No reactivity hazard other than the effects described in sub-sections below.
10.4. Conditions to avoid	
	Avoid moisture in installation systems.
10.5. Incompatible materials	
	Reacts with most metals in the presence of moisture, liberating hydrogen, an extremely flammable gas.
	For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity	ity : Classification criteria are not met.	
Hydrogen fluoride (7664-39-3)		
LC50 Inhalation - Rat [ppm]	483 ppm/4h	
Skin corrosion/irritation	Classification criteria are not met.	



250 - 500 ppm Hydrogen fluoride in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

Serious eye damage/irritation	: Classification criteria are not met.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
11.2. Information on other hazards	

No additional information available

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Assessment	: Classification criteria are not met.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.

# Hydrogen fluoride (7664-39-3) EC50 48h - Daphnia magna [mg/l] 97 - 352 mg/l EC50 72h - Algae [mg/l] 43 - 122 mg/l LC50 96 h - Fish [mg/l] 51 - 340 mg/l

Nitrogen (7727-37-9)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No data available.
<u>12.4. Mobility in soil</u>	
Assessment	: No data available.
Assessment	: No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
Assessment	:
12.7. Other adverse effects	
Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: No effect on the ozone layer.



250 - 500 ppm Hydrogen fluoride in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

Effect on global warming

: No known effects from this product.

13.1. Waste treatment methods	
ist of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	<ul> <li>May be vented to atmosphere in a well ventilated place.</li> <li>Do not discharge into any place where its accumulation could be dangerous.</li> <li>Return unused product in original container to supplier.</li> <li>16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.</li> </ul>
13.2. Additional information	
	External treatment and disposal of waste should comply with applicable local and/or national regulations.
SECTION 14: Transport information	
14.1. UN number or ID number	
n accordance with ADR / RID / IMDG / IATA / ADN JN-No.	: 1956
14.2. UN proper shipping name	
Fransport by road/rail (ADR/RID)	: COMPRESSED GAS, N.O.S. (Nitrogen, Hydrogen fluoride)
	: Compressed gas, n.o.s. (Nitrogen, Hydrogen fluoride)
	: COMPRESSED GAS, N.O.S. (Nitrogen, Hydrogen fluoride)
14.3. Transport hazard class(es)	
_abelling	
	2.2 : Non-flammable, non-toxic gases.
Transport by road/rail (ADR/RID) Class	: 2
Classification code	: 1A
	: 20
	: E - Passage forbidden through tunnels of category E
<b>Fransport by air (ICAO-TI / IATA-DGR)</b> Class / Div. (Sub. risk(s))	: 2.2
Fransport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.2
<b>ö</b> , (, ,	: F-C
	: S-V
14.4. Packing group	
Γransport by road/rail (ADR/RID) Γransport by air (ICAO-TI / IATA-DGR)	: Not applicable. : Not applicable.
	Not applicable.
14.5. Environmental hazards	
Fransport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
	: None.



# 250 - 500 ppm Hydrogen fluoride in

## Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

#### 14.6. Special precautions for user

Packing Instruction(s)	. 5000
Transport by road/rail (ADR/RID)	: P200.
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: 200.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200.
Special transport precautions	<ul> <li>Avoid transport on vehicles where the load space is not separated from the driver's compartment.</li> </ul>
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in
	the event of an accident or an emergency.
	Before transporting product containers:
	- Ensure there is adequate ventilation.
	- Ensure that containers are firmly secured.
	- Ensure valve is closed and not leaking.
	- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
	- Ensure valve protection device (where provided) is correctly fitted.
14.7. Maritime transport in bulk according to	o IMO instruments
	Net over the state

#### Not applicable.

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

FIL-Roo	ulations
EU-Reg	ulations

Eo Regulations	
Restrictions on use	: None.
Other information, restriction and prohibition regulations Seveso Directive : 2012/18/EU (Seveso III)	<ul> <li>Contains no substance on the REACH candidate list.</li> <li>Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.</li> <li>Not covered.</li> </ul>
National regulations	
Regulatory reference	: Ensure all national/local regulations are observed.
15.2. Chemical safety assessment	
	A CSA does not need to be carried out for this product.

## SECTION 16: Other information

Indication of changes

: Safety data sheet in accordance with commission regulation (EU) No 2020/878.



250 - 500 ppm Hydrogen fluoride in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

Abbreviations and acronyms	<ul> <li>ATE - Acute Toxicity Estimate.</li> <li>CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.</li> <li>REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.</li> <li>EINECS - European Inventory of Existing Commercial Chemical Substances.</li> <li>CAS# - Chemical Abstract Service number.</li> <li>PPE - Personal Protection Equipment.</li> <li>LC50 - Lethal Concentration to 50 % of a test population.</li> <li>RMM - Risk Management Measures.</li> <li>PBT - Persistent, Bioaccumulative and Toxic.</li> <li>vPvB - Very Persistent and Very Bioaccumulative.</li> <li>STOT- SE : Specific Target Organ Toxicity - Single Exposure.</li> <li>CSA - Chemical Safety Assessment.</li> <li>EN - European Standard.</li> <li>UN - United Nations.</li> <li>ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road.</li> <li>IATA - International Air Transport Association.</li> <li>IMDG code - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Road.</li> <li>IXTA - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Road.</li> <li>IXTA - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Road.</li> <li>IXTA - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.</li> <li>WGK - Water Hazard Class.</li> <li>STOT - RE : Specific Target Organ Toxicity - Repeated Exposure.</li> <li>UFI : Unique Formula Identifier.</li> </ul>
Training advice	<ul> <li>The hazard of asphyxiation is often overlooked and must be stressed during operator training.</li> <li>For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu</li> </ul>
Further information	<ul> <li>Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : http://www.eiga.eu.</li> <li>Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).</li> </ul>

Full text of H- and EUH-statements	
Acute Tox. 1 (Dermal)	Acute toxicity (dermal), Category 1
Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Acute Tox. 2 (Oral)	Acute toxicity (oral), Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H280	Contains gas under pressure; may explode if heated.
H300	Fatal if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
DISCLAIMER OF LIABILITY	<ul> <li>Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.</li> <li>Details given in this document are believed to be correct at the time of going to press.</li> </ul>

or damage resulting from its use can be accepted.

Whilst proper care has been taken in the preparation of this document, no liability for injury



250 - 500 ppm Hydrogen fluoride in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: 8499

End of document