

≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580 Issue date: 4/13/2016 Revision date: 1/12/2023 Supersedes version of: 8/23/2022 Version: 3.0





1.1. Product identifier	
SDS no	: SDS 00580
1.2. Relevant identifie	d uses of the substance or mixture and uses advised against
Relevant identified uses Uses advised against	
1.3. Details of the sup	plier of the safety data sheet
Air Liquide UK Ltd. Station Road Coleshill B46 1JY Birmingham United Kingdom <u>safety.aluk@airliquide.c</u>	<u>om</u>
1.4. Emergency teleph	none number
SECTION 2: Haza 2.1. Classification of t Classification accordin	rds identification he substance or mixture ng to Regulation (EC) No. 1272/2008 [CLP]
SECTION 2: Haza 2.1. Classification of t Classification accordin Physical hazards 2.2. Label elements	rds identification he substance or mixture ng to Regulation (EC) No. 1272/2008 [CLP]
SECTION 2: Haza 2.1. Classification of t Classification accordin Physical hazards 2.2. Label elements	rds identification he substance or mixture ng to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] The substance or mixture H280 H280 H280 H280 H280 H280 H280 H28
SECTION 2: Haza 2.1. Classification of t Classification accordin Physical hazards 2.2. Label elements Labelling according to Hazard pictograms (CLF) Signal word (CLP) Hazard statements (CLF) Precautionary statement	rds identification he substance or mixture ng to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] P) E Gases under pressure F Gases under pressure Gases under pressure CHS04 E Varning P) : H280 - Contains gas under pressure; may explode if heated. ts (CLP)
SECTION 2: Haza 2.1. Classification of t Classification accordin Physical hazards 2.2. Label elements Labelling according to Hazard pictograms (CLR Signal word (CLP) Hazard statements (CLR Precautionary statements - Storage	rds identification he substance or mixture ng to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] (F) (F)
SECTION 2: Haza 2.1. Classification of t Classification accordin Physical hazards 2.2. Label elements Labelling according to Hazard pictograms (CLF) Signal word (CLP) Hazard statements (CLF) Precautionary statement	rds identification he substance or mixture ng to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] P) E Gases under pressure F Gases under pressure Gases under pressure CHS04 E Varning P) : H280 - Contains gas under pressure; may explode if heated. ts (CLP)



≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Nitrogen	CAS-No.: 7727-37-9 EC-No.: 231-783-9 EC Index-No.: REACH-no: *1	79.02	Press. Gas (Comp.), H280
Oxygen	CAS-No.: 7782-44-7 EC-No.: 231-956-9 EC Index-No.: 008-001-00-8 REACH-no: *1	20.88	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Sulphur dioxide	CAS-No.: 7446-09-5 EC-No.: 231-195-2 EC Index-No.: 016-011-00-9 REACH-no: 01-2119485028-34	0.1	Press. Gas (Liq.), H280 Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 3 (Inhalation:gas), H331

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation - Skin contact - Eye contact - Ingestion	 Adverse effects not expected from this product. Adverse effects not expected from this product. Adverse effects not expected from this product. Ingestion is not considered a potential route of exposure.
	· ····

4.2. Most important symptoms and effects, both acute and delayed

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
- Suitable extinguishing media	: Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire.	
- Unsuitable extinguishing media	: Do not use water jet to extinguish.	
5.2. Special hazards arising from the su	bstance or mixture	
Specific hazards	: Supports combustion. Exposure to fire may cause containers to rupture/explode.	
Hazardous combustion products	: None that are more hazardous than the product itself.	



≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580

5.3. Advice for firefighters	
Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	 Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	: Act in accordance with local emergency plan. Stay upwind. See section 8 of the SDS for more information on personal protective equipment.	
For emergency responders	: See section 5.3 of the SDS for more information.	
6.2. Environmental precautions		
	None.	
6.3. Methods and material for containment and cleaning up		
	None.	
6.4. Reference to other sections		
	See also sections 8 and 13.	

7.1. Precautions for safe handling	
Safe use of the product	: Do not breathe gas.
	Avoid release of product into atmosphere.
	The product must be handled in accordance with good industrial hygiene and safety procedures.
	Only experienced and properly instructed persons should handle gases under pressure.
	Consider pressure relief device(s) in gas installations.
	Ensure the complete gas system was (or is regularily) checked for leaks before use.
	Do not smoke while handling product.
	Use only properly specified equipment which is suitable for this product, its supply pressure
	and temperature. Contact your gas supplier if in doubt.
	Use only oxygen approved lubricants and oxygen approved sealings.
	Avoid suck back of water, acid and alkalis.



≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580

Safe handling of the gas receptacle	: Refer to supplier's container handling instructions.
	Do not allow backfeed into the container.
	Protect containers from physical damage; do not drag, roll, slide or drop.
	When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.)
	designed to transport cylinders.
	Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
	If user experiences any difficulty operating valve discontinue use and contact supplier.
	Never attempt to repair or modify container valves or safety relief devices.
	Damaged valves should be reported immediately to the supplier.
	Keep container valve outlets clean and free from contaminants particularly oil and water.
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another.
	Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content
	of the container.
	Suck back of water into the container must be prevented.
	Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, including any i	ncompatibilities
	Observe all regulations and local requirements regarding storage of containers.
	Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place.
	Containers should be stored in the vertical position and properly secured to prevent them from falling over.
	Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place.
	Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.
7.3. Specific end use(s)	

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sulphur dioxide (7446-09-5)	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	2.7 mg/m ³
Long-term - local effects, inhalation	2.7 mg/m ³

PNEC (Predicted No-Effect Concentration)

: None established.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.



≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580

Eye/face protection	: Wear safety glasses with side shields.
	Standard EN 166 - Personal eye-protection - specifications.
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers.
	Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
- Other	: Wear safety shoes while handling containers.
	Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	: Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
	Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
	Gas filters do not protect against oxygen deficiency.
	Never use any kind of filtering respiratory protection equipment when working with this substance due to it having poor or no warning properties.
	Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .
Thermal hazards	: None in addition to the above sections.
8.2.3. Environmental exposure controls	

None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance - Physical state at 20°C / 101.3kPa	: Gas.
- Colour	: Colourless.
Odour	
Odoui	: Odour threshold is subjective and inadequate to warn of overexposure.
	Mixture contains one or more component(s) which have the following odour:
Malting point / Franzing point	Pungent.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
	It is technically not possible to determine the boiling point or range of this mixtur
	Component with lowest boiling point: Nitrogen -196 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available.
Upper explosion limit	: Not available.
Flash point	: Not applicable for gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
рН	: Not applicable for gas mixtures.
Viscosity, kinematic	: Not applicable.
Water solubility [20°C]	: Mixture is partially soluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable.
Relative vapour density (air=1)	: Lighter or similar to air.
Particle characteristics	: Not applicable.

9.2. Other information

9.2.1. Information with regard to physical hazard classes	
Explosive properties	: Not applicable.
Explosion limits	: Non flammable.
Oxidising properties	: Not applicable.
9.2.2. Other safety characteristics	

9.2.2. Other	' safety	characteristics
--------------	----------	-----------------

Molar mass	:	Not applicable for gas mixtures.
Evaporation rate	:	Not applicable for gas mixtures.



≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580

Other data

: None.

SECTION 10: Stability and reactivity	
10.1. Reactivity	
	No reactivity hazard other than the effects described in sub-sections below. Data for mixture are not available. This mixture contains components with the following reactivity : Violently oxidises organic material.
<u>10.2. Chemical stability</u>	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	None.
10.4. Conditions to avoid	
	Avoid moisture in installation systems.
10.5. Incompatible materials	
	For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity	: Classification criteria are not met.	
Sulphur dioxide (7446-09-5)		
LC50 Inhalation - Rat [ppm]	1260 ppm/4h	
Skin corrosion/irritation	: Classification criteria are not met.	
Serious eye damage/irritation	: Classification criteria are not met.	
Respiratory or skin sensitisation	: No known effects from this product.	
Germ cell mutagenicity	: No known effects from this product.	
Carcinogenicity	: No known effects from this product.	
Toxic for reproduction : Fertility	: No known effects from this product.	
Toxic for reproduction : unborn child	: No known effects from this product.	

: No known effects from this product.

: No known effects from this product.

: Not applicable for gases and gas mixtures.

STOT-repeated exposure Aspiration hazard

STOT-single exposure

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Assessment
EC50 48h - Daphnia magna [mg/l]
EC50 72h - Algae [mg/l]

: No data available.

: No data available.

: Classification criteria are not met.



≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580

LC50 96 h - Fish [mg/l]

: No data available.

Sulphur dioxide (7446-09-5)	
EC50 48h - Daphnia magna [mg/l]	89 mg/l
EC50 72h - Algae [mg/l]	48.1 mg/l
LC50 96 h - Fish [mg/l]	No data available.

Oxygen (7782-44-7)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

Nitrogen (7727-37-9)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

12.2. Persistence and degradability

Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No data available.
<u>12.4. Mobility in soil</u>	
Assessment	: No data available.
Assessment	: No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
Assessment	:
12.7. Other adverse effects	
Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: No effect on the ozone layer.
Effect on global warming	: No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
	May be vented to atmosphere in a well ventilated place.
	Do not discharge into any place where its accumulation could be dangerous.
	Return unused product in original container to supplier.
List of hazardous waste codes (from Commission	: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.
Decision 2000/532/EC as amended)	
13.2. Additional information	

External treatment and disposal of waste should comply with applicable local and/or national regulations.



: 1956

≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN UN-No.

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

COMPRESSED GAS, N.O.S. (Nitrogen, Sulphur dioxide) Compressed gas, n.o.s. (Nitrogen, Sulphur dioxide) COMPRESSED GAS, N.O.S. (Nitrogen, Sulphur dioxide)

14.3. Transport hazard class(es)

Transport by road/rail (ADR/RID)

Transport by air (ICAO-TI / IATA-DGR)

Hazard identification number

Class / Div. (Sub. risk(s))

Transport by sea (IMDG) Class / Div. (Sub. risk(s))

14.4. Packing group

Transport by sea (IMDG)

Emergency Schedule (EmS) - Fire

Transport by road/rail (ADR/RID)

<u>14.5. Environmental hazards</u> Transport by road/rail (ADR/RID)

Emergency Schedule (EmS) - Spillage

Transport by air (ICAO-TI / IATA-DGR)

Labelling

Class

Classification code

Tunnel Restriction



2.2 : Non-flammable, non-toxic gases.

- : 2
- : 1A
- : 20
- : E Passage forbidden through tunnels of category E
- : 2.2
- : 2.2
- : F-C
- : S-V
- : Not applicable.
 - Not applicable.
- : Not applicable.
- : None.
- : None.
- : None.
- 14.6. Special precautions for user

Transport by air (ICAO-TI / IATA-DGR)

Packing Instruction(s)

Transport by sea (IMDG)

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft Cargo Aircraft only Transport by sea (IMDG)

Special transport precautions

- : None
- : P200.
- : 200.
- : 200.
- : P200.
- : Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

- Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.



≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

ons/legislation specific for the substance or mixture
 None. Contains no substance on the REACH candidate list. Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals. Not covered.
: Ensure all national/local regulations are observed.
A CSA does not need to be carried out for this product.
: Safety data sheet in accordance with commission regulation (EU) No 2020/878.
 ATE - Acute Toxicity Estimate. CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. EINECS - European Inventory of Existing Commercial Chemical Substances. CAS# - Chemical Abstract Service number. PPE - Personal Protection Equipment. LC50 - Lethal Concentration to 50 % of a test population. RMM - Risk Management Measures. PBT - Persistent, Bioaccumulative and Toxic. vPVB - Very Persistent and Very Bioaccumulative. STOT - SE : Specific Target Organ Toxicity - Single Exposure. CSA - Chemical Safety Assessment. EN - European Standard. UN - United Nations. ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road. IATA - International Air Transport Association. IMDG code - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Road. INTA - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Road. IATA - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Road. ID - Regulations concerning the International Carriage of Dangerous Goods by Road. ID - Regulations concerning the International Carriage of Dangerous Goods by Road. WGK - Water Hazard Class. STOT - RE : Specific Target Organ Toxicity - Repeated Exposure. UFI : Unique Formula Identifier. None.

Training advice Further information

: Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : http://www.eiga.eu.

Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).

Full text of H- and EUH-statements	
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1



≤ 1000 ppm Sulphur dioxide in Air

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 00580

H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B

DISCLAIMER OF LIABILITY

 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document