

8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218 Issue date: 5/28/2020 Revision date: 1/13/2023 Supersedes version of: 8/25/2022 Version: 3.0





| 1.1. Product identifier | | |
|---|---|------|
| SDS no | : SDS 01218 | |
| 1.2. Relevant identified u | uses of the substance or mixture and uses advised against | |
| Relevant identified uses Uses advised against | Industrial and professional uses. Perform risk assessment prior to use.Consumer use. | |
| | Uses other than those listed above are not supported, contact your supplier for information on other uses. | more |
| 1.3. Details of the suppli | ier of the safety data sheet | |
| Air Liquide UK Ltd. | | |
| Station Road Coleshill | | |
| B46 1JY Birmingham United Kingdom | | |
| safety.aluk@airliquide.con | <u>n</u> | |
| 1.4. Emergency telephor | ne number | |
| _ , | | |
| | | |
| Emergency telephone nun SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards | ds identification | |
| SECTION 2: Hazard 2.1. Classification of the Classification according | ds identification e substance or mixture g to Regulation (EC) No. 1272/2008 [CLP] | |
| SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards 2.2. Label elements | ds identification e substance or mixture g to Regulation (EC) No. 1272/2008 [CLP] | |
| SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards 2.2. Label elements | ds identification e substance or mixture g to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] | |
| SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards 2.2. Label elements Labelling according to R | ds identification e substance or mixture g to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] | |
| SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards 2.2. Label elements Labelling according to R | ds identification e substance or mixture g to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] : : : : : : : : : : : : : | |
| SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards 2.2. Label elements Labelling according to R | ds identification e substance or mixture g to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] | |
| SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards 2.2. Label elements Labelling according to R Hazard pictograms (CLP) | As identification e substance or mixture g to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] GHS04 : Warning : H280 - Contains gas under pressure; may explode if heated. (CLP) | |
| SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards 2.2. Label elements Labelling according to R Hazard pictograms (CLP) Signal word (CLP) Hazard statements (CLP) | ds identification e substance or mixture to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] GHS04 : Warning : H280 - Contains gas under pressure; may explode if heated. | |
| SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards 2.2. Label elements Labelling according to R Hazard pictograms (CLP) Signal word (CLP) Hazard statements (CLP) Precautionary statements | As identification e substance or mixture g to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] GHS04 : Warning : H280 - Contains gas under pressure; may explode if heated. (CLP) | |
| SECTION 2: Hazard 2.1. Classification of the Classification according Physical hazards 2.2. Label elements Labelling according to R Hazard pictograms (CLP) Signal word (CLP) Hazard statements (CLP) Precautionary statements | ds identification e substance or mixture g to Regulation (EC) No. 1272/2008 [CLP] Gases under pressure : Compressed gas H280 Regulation (EC) No. 1272/2008 [CLP] GHS04 : Warning : H280 - Contains gas under pressure; may explode if heated. (CLP) | |



8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|----------|---|------|--|
| Nitrogen | CAS-No.: 7727-37-9 EC-No.: 231-783-9 EC Index-No.: REACH-no: *1 | 91.5 | Press. Gas (Comp.), H280 |
| Methane | CAS-No.: 74-82-8 EC-No.: 200-812-7 EC Index-No.: 601-001-00-4 REACH-no: 01-2119474442-39 | 8.5 | Flam. Gas 1A, H220 Press. Gas (Comp.), H280 |

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

| 4.1. Description of first aid measures | |
|--|--|
| - Inhalation | Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped. |
| - Skin contact | : Adverse effects not expected from this product. |
| - Eye contact | : Adverse effects not expected from this product. |
| - Ingestion | : Ingestion is not considered a potential route of exposure. |
| 4.2. Most important symptoms and effects | , both acute and delayed |

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

| SECTION 5: Firefighting measures | | |
|--|--|--|
| 5.1. Extinguishing media | | |
| - Suitable extinguishing media | : Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire. | |
| - Unsuitable extinguishing media | : Do not use water jet to extinguish. | |
| 5.2. Special hazards arising from the substance or mixture | | |
| Specific hazards Hazardous combustion products | Exposure to fire may cause containers to rupture/explode. Incomplete combustion may form carbon monoxide. | |



8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218

| 5.3. Advice for firefighters | |
|--|---|
| Specific methods | Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk. |
| Special protective equipment for fire fighters | In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. |

SECTION 6: Accidental release measures

| 6.1. Personal precautions, protective equipment and emergency procedures | | |
|--|--|--|
| For non-emergency personnel | : Act in accordance with local emergency plan. Try to stop release. | |
| | Evacuate area | |
| | Ensure adequate air ventilation. | |
| | Stay upwind. | |
| | See section 8 of the SDS for more information on personal protective equipment. | |
| For emergency responders | : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. | |
| | Oxygen detectors should be used when asphyxiating gases may be released. | |
| | See section 5.3 of the SDS for more information. | |
| 6.2. Environmental precautions | | |
| | Try to stop release. | |
| 6.3. Methods and material for containment and cleaning up | | |
| | Ventilate area. | |
| 6.4. Reference to other sections | | |
| | See also sections 8 and 13. | |
| | | |

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| Safe use of the product | : Do not breathe gas. |
|-------------------------|--|
| | Avoid release of product into atmosphere. |
| | The product must be handled in accordance with good industrial hygiene and safety procedures. |
| | Only experienced and properly instructed persons should handle gases under pressure. |
| | Consider pressure relief device(s) in gas installations. |
| | Ensure the complete gas system was (or is regularily) checked for leaks before use. |
| | Do not smoke while handling product. |
| | Use only properly specified equipment which is suitable for this product, its supply pressure |
| | and temperature. Contact your gas supplier if in doubt. |
| | Avoid suck back of water, acid and alkalis. |



8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218

| Safe handling of the gas receptacle | Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock. |
|---|---|
| 7.2. Conditions for safe storage, including any inc | ompatibilities |
| | Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials. |
| 7.3. Specific end use(s) | |
| | None. |

| SECTION 8: Exposure controls/personal protection | |
|---|---|
| 8.1. Control parameters | |
| DNEL (Derived-No Effect Level) | : None established. |
| PNEC (Predicted No-Effect Concentration) | : None established. |
| 8.2. Exposure controls | |
| 8.2.1. Appropriate engineering controls | |
| | Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities. |
| 8.2.2. Individual protection measures, e.g. persona | al protective equipment |
| | A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. |
| Eye/face protection | : Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications. |
| Skin protection | |



8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218

| - Hand protection | : Wear working gloves when handling gas containers. |
|--|--|
| | Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher. |
| - Other | : Wear safety shoes while handling containers. |
| | Standard EN ISO 20345 - Personal protective equipment - Safety footwear. |
| Respiratory protection | : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known. |
| | Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers. |
| | Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full |
| | face mask. |
| | Gas filters do not protect against oxygen deficiency. |
| | Never use any kind of filtering respiratory protection equipment when working with this substance due to it having poor or no warning properties. |
| | Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. |
| | Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks . |
| Thermal hazards | : None in addition to the above sections. |
| 8.2.3. Environmental exposure controls | |

None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| · · · | |
|---|--|
| Appearance | |
| - Physical state at 20°C / 101.3kPa | : Gas. |
| - Colour | : Colourless. |
| Odour | : Odourless. |
| Melting point / Freezing point | : Not applicable for gas mixtures. |
| Boiling point | : Not applicable for gas mixtures. |
| | It is technically not possible to determine the boiling point or range of this mixture. Component with lowest boiling point: Nitrogen -196 °C |
| Flommobility | : Non flammable. |
| Flammability Lower explosion limit | : Not available. |
| • | : Not available. |
| Upper explosion limit | |
| Flash point Auto-ignition temperature | : Not applicable for gases and gas mixtures. : Non flammable. |
| Decomposition temperature | : Not applicable. |
| pH | : Not applicable. : Not applicable for gases and gas mixtures. |
| Viscosity, kinematic | : No reliable data available. |
| Water solubility [20°C] | : Mixture is partially soluble in water |
| Partition coefficient n-octanol/water (Log Kow) | : Not applicable for gas mixtures. |
| Vapour pressure [20°C] | : Not applicable. |
| Vapour pressure [50°C] | : Not applicable. |
| Density and/or relative density | : Not applicable. |
| Relative vapour density (air=1) | : Lighter or similar to air. |
| Particle characteristics | : Not applicable. |
| 9.2. Other information | |
| 9.2.1. Information with regard to physical haza | rd classes |
| Explosive properties | : Not applicable. |
| Explosion limits | : Non flammable. |
| Oxidising properties | : Not applicable. |
| 9.2.2. Other safety characteristics | |
| Molar mass | : Not applicable for gas mixtures. |



8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218

| SECTION 10: Stability and reactivity | |
|--|--|
| 10.1. Reactivity | |
| | No reactivity hazard other than the effects described in sub-sections below. Data for mixture are not available. This mixture contains components with the following reactivity : Can form explosive mixture with air. May react violently with oxidants. |
| 10.2. Chemical stability | |
| | Stable under normal conditions. |
| 10.3. Possibility of hazardous reactions | |
| | None. |
| 10.4. Conditions to avoid | |
| | Avoid moisture in installation systems. |
| 10.5. Incompatible materials | |
| | For additional information on compatibility refer to ISO 11114. |
| 10.6. Hazardous decomposition products | |
| | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

SECTION 11: Toxicological information 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

| Acute toxicity | : Toxicological effects not expected from this product if occupational exposure limit values are not exceeded. |
|---------------------------------------|--|
| Skin corrosion/irritation | : No known effects from this product. |
| Serious eye damage/irritation | : No known effects from this product. |
| Respiratory or skin sensitisation | : No known effects from this product. |
| Germ cell mutagenicity | : No known effects from this product. |
| Carcinogenicity | : No known effects from this product. |
| Toxic for reproduction : Fertility | : No known effects from this product. |
| Toxic for reproduction : unborn child | : No known effects from this product. |
| STOT-single exposure | : No known effects from this product. |
| STOT-repeated exposure | : No known effects from this product. |
| Aspiration hazard | : Not applicable for gases and gas mixtures. |
| 11.2. Information on other hazards | |

No additional information available

| SECTION 12: Ecological informa | tion |
|---------------------------------|--|
| 12.1. Toxicity | |
| Assessment | : Classification criteria are not met. |
| EC50 48h - Daphnia magna [mg/l] | : No data available. |
| EC50 72h - Algae [mg/l] | : No data available. |
| LC50 96 h - Fish [mg/l] | : No data available. |
| Methane (74-82-8) | |
| EC50 48h - Daphnia magna [mg/l] | 69.4 mg/l |



8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218

| Methane (74-82-8) | | |
|--|--|--|
| EC50 72h - Algae [mg/l] | 19.4 mg/l | |
| LC50 96 h - Fish [mg/l] | 147.5 mg/l | |
| Nitrogen (7727-37-9) | | |
| EC50 48h - Daphnia magna [mg/l] | No data available. | |
| EC50 72h - Algae [mg/l] | No data available. | |
| LC50 96 h - Fish [mg/l] | No data available. | |
| 12.2. Persistence and degradability | | |
| Assessment : | No ecological damage caused by this product. | |
| 12.3. Bioaccumulative potential | | |
| Assessment : | No data available. | |
| 12.4. Mobility in soil | | |
| Assessment : | No ecological damage caused by this product. | |
| 12.5. Results of PBT and vPvB assessment | | |
| Assessment : | Not classified as PBT or vPvB. | |
| 12.6. Endocrine disrupting properties | | |
| Assessment | | |
| 12.7. Other adverse effects | | |
| Other adverse effects : | No known effects from this product. | |
| Effect on the ozone layer : | No effect on the ozone layer. | |
| Effect on global warming : | Contains greenhouse gas(es). | |

| SECTION 13: | Disposal | considerations |
|-------------|----------|----------------|
| | Disposul | oonsiderations |

| 13.1. Waste treatment methods | |
|--|---|
| | May be vented to atmosphere in a well ventilated place. |
| | Do not discharge into any place where its accumulation could be dangerous. |
| | Return unused product in original container to supplier. |
| List of hazardous waste codes (from Commission | : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04. |
| Decision 2000/532/EC as amended) | |
| | |

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN UN-No. : 1956



8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

- : COMPRESSED GAS, N.O.S. (Nitrogen, Methane)
- : Compressed gas, n.o.s. (Nitrogen, Methane)
- : COMPRESSED GAS, N.O.S. (Nitrogen, Methane)

14.3. Transport hazard class(es)

Labelling

| Transport by road/rail (ADR/RID |)) |
|---------------------------------|----|
| Class | |

Classification code Hazard identification number Tunnel Restriction

Transport by air (ICAO-TI / IATA-DGR) Class / Div. (Sub. risk(s))

Transport by sea (IMDG)

| Class / Div. (Sub. risk(s)) |
|-------------------------------------|
| Emergency Schedule (EmS) - Fire |
| Emergency Schedule (EmS) - Spillage |

14.4. Packing group

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

14.5. Environmental hazards

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft Cargo Aircraft only Transport by sea (IMDG)

Special transport precautions

- 2.2 : Non-flammable, non-toxic gases. : 2 : 1A : 20 : E - Passage forbidden through tunnels of category E : 2.2 : 2.2 · F-C : S-V : Not applicable. : Not applicable. : Not applicable. : None. : None. : None. : P200. : 200. : 200. : P200. : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure valve is closed and not leaking.
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 - Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.



8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| EU-Regulations | |
|---|--|
| Restrictions on use | : None. Contains no substance on the REACH candidate list. |
| Other information, restriction and prohibition regulations Seveso Directive : 2012/18/EU (Seveso III) | Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals. Not covered. |
| National regulations | |
| Regulatory reference | : Ensure all national/local regulations are observed. |
| 15.2. Chemical safety assessment | |
| | A CSA does not need to be carried out for this product. |

| Indication of changes | : Safety data sheet in accordance with commission regulation (EU) No 2020/878. |
|----------------------------|---|
| Abbreviations and acronyms | : ATE - Acute Toxicity Estimate. |
| | CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. |
| | EINECS - European Inventory of Existing Commercial Chemical Substances. |
| | CAS# - Chemical Abstract Service number. |
| | PPE - Personal Protection Equipment. |
| | LC50 - Lethal Concentration to 50 % of a test population. |
| | RMM - Risk Management Measures. |
| | PBT - Persistent, Bioaccumulative and Toxic. |
| | vPvB - Very Persistent and Very Bioaccumulative. |
| | STOT- SE : Specific Target Organ Toxicity - Single Exposure. |
| | CSA - Chemical Safety Assessment. |
| | EN - European Standard. |
| | UN - United Nations. |
| | ADR - European Agreement concerning the International Carriage of Dangerous Goods b Road. |
| | IATA - International Air Transport Association. |
| | IMDG code - International Maritime Dangerous Goods. |
| | RID - Regulations concerning the International Carriage of Dangerous Goods by Rail. WGK - Water Hazard Class. |
| | STOT - RE : Specific Target Organ Toxicity - Repeated Exposure. |
| | UFI : Unique Formula Identifier. |
| Training advice | : The hazard of asphyxiation is often overlooked and must be stressed during operator training. |
| | For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu |
| Further information | : Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : http://www.eiga.eu. |
| | Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). |

| Full text of H- and EUH-statements | |
|------------------------------------|------------------------------|
| Flam. Gas 1A | Flammable gases, Category 1A |
| H220 | Extremely flammable gas. |



8.5% Methane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01218

| H280 | Contains gas under pressure; may explode if heated. |
|-------------------------|---|
| Press. Gas (Comp.) | Gases under pressure : Compressed gas |
| DISCLAIMER OF LIABILITY | Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. |

End of document