

### ≤15% Oxygen, ≤300 ppm Propane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462 Issue date: 7/5/2023 Version: 1.0

### Warning



SECTION 1: Identif	cation of the substance/mixture and of the company/undertaking
1.1. Product identifier	
SDS no	: SDS 01462
1.2. Relevant identified	uses of the substance or mixture and uses advised against
Relevant identified uses Uses advised against	<ul> <li>Industrial and professional uses. Perform risk assessment prior to use.</li> <li>Consumer use.</li> <li>Uses other than those listed above are not supported, contact your supplier for more information on other uses.</li> </ul>
1.3. Details of the suppl	er of the safety data sheet
Air Liquide UK Ltd. Station Road Coleshill B46 1JY Birmingham United Kingdom safety.aluk@airliquide.cor	
1.4. Emergency telepho	<u>ne number</u>
Emergency telephone nur	nber : 01675 462695 (Available 24/7)
SECTION 2: Hazard	s identification
2.1. Classification of the	substance or mixture
Classification according	to Regulation (EC) No. 1272/2008 [CLP]
Physical hazards	Gases under pressure : Compressed gas H280
2.2. Label elements	
Labelling according to R	egulation (EC) No. 1272/2008 [CLP]
Hazard pictograms (CLP)	GHS04
Signal word (CLP)	: Warning
Hazard statements (CLP)	: H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP) - Storage

#### 2.3. Other hazards

: P403 - Store in a well-ventilated place.

Asphyxiant in high concentrations. Not classified as PBT or vPvB.



≤15% Oxygen, ≤300 ppm Propane in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462

#### **SECTION 3: Composition/information on ingredients**

3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Nitrogen	CAS-No.: 7727-37-9 EC-No.: 231-783-9 EC Index-No.: REACH-no: *1	84.97	Press. Gas (Comp.), H280
Oxygen	CAS-No.: 7782-44-7 EC-No.: 231-956-9 EC Index-No.: 008-001-00-8 REACH-no: *1	15	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Propane	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	0.03	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped

	stopped.
- Skin contact	: Adverse effects not expected from this product.
E de la contra et	A design of the state of the second state of t

- Eye contact
   Adverse effects not expected from this product.
   Ingestion
   Ingestion is not considered a potential route of exposure.
- Ingestion shot considered a potential rou

#### 4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
- Suitable extinguishing media	: Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire.	
- Unsuitable extinguishing media	: Do not use water jet to extinguish.	
5.2. Special hazards arising from the substance or mixture		
Specific hazards	: Exposure to fire may cause containers to rupture/explode.	



# ≤15% Oxygen, ≤300 ppm Propane in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462

Hazardous combustion products	: Incomplete combustion may form carbon monoxide.
5.3. Advice for firefighters	
Specific methods	<ul> <li>Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.</li> <li>If possible, stop flow of product.</li> <li>Use water spray or fog to knock down fire fumes if possible.</li> <li>Move containers away from the fire area if this can be done without risk.</li> </ul>
Special protective equipment for fire fighters	<ul> <li>In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</li> <li>Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.</li> </ul>

#### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	: Act in accordance with local emergency plan. Try to stop release.	
	Evacuate area.	
	Ensure adequate air ventilation.	
	Stay upwind.	
	See section 8 of the SDS for more information on personal protective equipment.	
For emergency responders	: Wear self-contained breathing apparatus when entering area unless atmosphere is proved	
	to be safe.	
	Oxygen detectors should be used when asphyxiating gases may be released.	
	See section 5.3 of the SDS for more information.	
6.2. Environmental precautions		
	Try to stop release.	
6.3. Methods and material for containment and cleaning up		
	Ventilate area.	
6.4. Reference to other sections		
	See also sections 8 and 13.	

### SECTION 7: Handling and storage

7.1. Precautions for safe handling	
	Do not breathe gas. Avoid release of product into atmosphere. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Use only oxygen approved lubricants and oxygen approved sealings. Avoid suck back of water, acid and alkalis.



### ≤15% Oxygen, ≤300 ppm Propane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462

Conditions for safe storage, including any incompatibilities         Observe all regulations and local requirements regarding storage of containers.         Containers should not be stored in conditions likely to encourage corrosion.         Container valve guards or caps should be in place.         Containers should be stored in the vertical position and properly secured to prevent them from falling over.         Stored containers should be periodically checked for general condition and leakage.         Keep container below 50°C in a well ventilated place.         Store containers in location free from fire risk and away from sources of heat and ignition.         Keep away from combustible materials.	Safe handling of the gas receptacle	<ul> <li>Refer to supplier's container handling instructions.</li> <li>Do not allow backfeed into the container.</li> <li>Protect containers from physical damage; do not drag, roll, slide or drop.</li> <li>When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.</li> <li>Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.</li> <li>If user experiences any difficulty operating valve discontinue use and contact supplier.</li> <li>Never attempt to repair or modify container valves or safety relief devices.</li> <li>Damaged valves should be reported immediately to the supplier.</li> <li>Keep container valve outlets clean and free from contaminants particularly oil and water.</li> <li>Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.</li> <li>Close container valve after each use and when empty, even if still connected to equipment.</li> <li>Never use direct flame or electrical heating devices to raise the pressure of a container.</li> <li>Do not remove or deface labels provided by the supplier for the identification of the content of the container.</li> </ul>
Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.	7.2 Conditions for safe storage including any inc	
		Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition.
	7.3. Specific end use(s)	None.

**SECTION 8: Exposure controls/personal protection** 8.1. Control parameters DNEL (Derived-No Effect Level) : None established. PNEC (Predicted No-Effect Concentration) : None established. 8.2. Exposure controls 8.2.1. Appropriate engineering controls Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities. 8.2.2. Individual protection measures, e.g. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. · Eye/face protection : Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications. Skin protection



# ≤15% Oxygen, ≤300 ppm Propane in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462

- Hand protection	<ul> <li>Wear working gloves when handling gas containers.</li> <li>Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.</li> <li>Wear safety shoes while handling containers.</li> <li>Standard EN ISO 20345 - Personal protective equipment - Safety footwear.</li> </ul>
Respiratory protection	<ul> <li>Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.</li> <li>Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.</li> <li>Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</li> <li>Gas filters do not protect against oxygen deficiency.</li> <li>Never use any kind of filtering respiratory protection equipment when working with this substance due to it having poor or no warning properties.</li> <li>Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.</li> <li>Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .</li> </ul>
Thermal hazards	: None in addition to the above sections.
8.2.3. Environmental exposure controls	

None necessary.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas.
- Colour	: Colourless.
Odour	: Odour threshold is subjective and inadequate to warn of overexposure.
	Mixture contains one or more component(s) which have the following odour:
	Stenchant often added. Sweetish.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
	It is technically not possible to determine the boiling point or range of this mixture.
	Component with lowest boiling point: Nitrogen -196 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available.
Upper explosion limit	: Not available.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
рН	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: Not known.
Water solubility [20°C]	: Mixture is partially soluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not available.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable.
Relative vapour density (air=1)	: Lighter or similar to air.
Particle characteristics	: Not applicable.

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Explosive properties	: Not applicable.
Explosion limits	: Non flammable.
Oxidising properties	: Not applicable.



≤15% Oxygen, ≤300 ppm Propane in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462

<b>9.2.2. Other safety characteristics</b> Molar mass Evaporation rate Other data	<ul><li>Not applicable for gas mixtures.</li><li>Not applicable for gases and gas mixtures.</li><li>None.</li></ul>
SECTION 10: Stability and reactivity	
10.1. Reactivity	
	No reactivity hazard other than the effects described in sub-sections below. Data for mixture are not available. This mixture contains components with the following reactivity : Can form explosive mixture with air. May react violently with oxidants. Violently oxidises organic material.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	Maria
	None.
10.4. Conditions to avoid	Avoid moisture in installation systems.
10.5. Incompatible materials	
	For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information
---------------------------------------

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	: Classification criteria are not met.
Propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	20000 ppm/4h
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
11.2. Information on other hazards	

No additional information available



≤15% Oxygen, ≤300 ppm Propane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462

#### **SECTION 12: Ecological information**

### 12.1. Toxicity

Assessment	: Classification criteria are not met.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.

Propane (74-98-6)	
EC50 48h - Daphnia magna [mg/l]	27.1 mg/l
EC50 72h - Algae [mg/l]	11.9 mg/l
LC50 96 h - Fish [mg/l]	49.9 mg/l

Oxygen (7782-44-7)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

Nitrogen (7727-37-9)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.
12.2. Persistence and degradability	·
Assessment :	No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment :	No data available.
12.4. Mobility in soil	
Assessment :	No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessment	
Assessment :	Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
Assessment :	
12.7. Other adverse effects	
Other adverse effects :	No known effects from this product.
Effect on the ozone layer :	No effect on the ozone layer.
Effect on global warming :	Contains greenhouse gas(es).

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Return unused product in original container to supplier.



≤15% Oxygen, ≤300 ppm Propane in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)

: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

#### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

#### **SECTION 14: Transport information**

14.1. UN number or ID number	
In accordance with ADR / RID / IMDG / IATA / ADN UN-No.	: 1956
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	: COMPRESSED GAS, N.O.S. (Nitrogen, Propane)
Transport by air (ICAO-TI / IATA-DGR)	: Compressed gas, n.o.s. (Nitrogen, Propane)
Transport by sea (IMDG)	: COMPRESSED GAS, N.O.S. (Nitrogen, Propane)
14.3. Transport hazard class(es)	
Labelling	: 2.2 : Non-flammable, non-toxic gases.
Transport by road/rail (ADR/RID)	
Class	: 2
Classification code	: 1A
Hazard identification number Tunnel Restriction	: 20 : E - Passage forbidden through tunnels of category E
Transport by air (ICAO-TI / IATA-DGR)	. E - Passage forbidden tillough tunnels of category E
Class / Div. (Sub. risk(s))	: 2.2
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.2
Emergency Schedule (EmS) - Fire	: F-C
Emergency Schedule (EmS) - Spillage	: S-V
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable.
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable.
Transport by sea (IMDG)	: Not applicable.
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None. : None.
Transport by sea (IMDG)	. None.
14.6. Special precautions for user	
Packing Instruction(s)	<b>5</b>
Transport by road/rail (ADR/RID)	: P200.
Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft	: 200.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200.



# ≤15% Oxygen, ≤300 ppm Propane in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462

Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment.
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in
	the event of an accident or an emergency.
	Before transporting product containers:
	- Ensure there is adequate ventilation.
	- Ensure that containers are firmly secured.
	<ul> <li>Ensure valve is closed and not leaking.</li> </ul>
	<ul> <li>Ensure valve outlet cap nut or plug (where provided) is correctly fitted.</li> </ul>
	<ul> <li>Ensure valve protection device (where provided) is correctly fitted.</li> </ul>
14.7. Maritime transport in bulk accord	ding to IMO instruments
	Not applicable.
SECTION 15: Regulatory inform	mation
15.1. Safety, health and environmenta	I regulations/legislation specific for the substance or mixture
EU-Regulations	
Restrictions on use	: None.

Restrictions on use	. None.
	Contains no substance on the REACH candidate list.
Other information, restriction and prohibition regulations Seveso Directive : 2012/18/EU (Seveso III)	<ul> <li>Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.</li> <li>Not covered.</li> </ul>
National regulations	
Regulatory reference	: Ensure all national/local regulations are observed.
15.2. Chemical safety assessment	
	A CSA does not need to be carried out for this product.

SECTION 16: Other information	
Indication of changes	: Safety data sheet in accordance with commission regulation (EU) No 2020/878.
Abbreviations and acronyms	<ul> <li>ATE - Acute Toxicity Estimate.</li> <li>CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.</li> <li>REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.</li> <li>EINECS - European Inventory of Existing Commercial Chemical Substances.</li> <li>CAS# - Chemical Abstract Service number.</li> <li>PPE - Personal Protection Equipment.</li> <li>LC50 - Lethal Concentration to 50 % of a test population.</li> <li>RMM - Risk Management Measures.</li> <li>PBT - Persistent, Bioaccumulative and Toxic.</li> <li>vPvB - Very Persistent and Very Bioaccumulative.</li> <li>STOT- SE : Specific Target Organ Toxicity - Single Exposure.</li> <li>CSA - Chemical Safety Assessment.</li> <li>EN - European Standard.</li> <li>UN - United Nations.</li> <li>ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road.</li> <li>IATA - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Road.</li> <li>IATA - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Road.</li> <li>IATA - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Road.</li> <li>IATA - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.</li> <li>WGK - Water Hazard Class.</li> <li>STOT - RE : Specific Target Organ Toxicity - Repeated Exposure.</li> <li>UFI : Unique Formula Identifier.</li> </ul>



≤15% Oxygen, ≤300 ppm Propane in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01462

Training advice	: The hazard of asphyxiation is often overlooked and must be stressed during operator
	training. For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at
	http://www.eiga.eu
Further information	: Classification using data from databases maintained by the European Industrial Gases
	Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling
	Guide', downloadable at : http://www.eiga.eu.
	Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).

Full text of H- and EUH-statements	
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

#### DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document