

# LASAL 2001

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01496 Issue date: 10/23/2023 Supersedes version of: 10/23/2023 Version: 1.0

# Warning

Г



SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
Trade name SDS no Other means of identification	<ul> <li>LASAL 2001</li> <li>SDS 01496</li> <li>Nitrogen</li> <li>CAS-No. : 7727-37-9</li> <li>EC-No. : 231-783-9</li> <li>EC Index-No. :</li> </ul>	
REACH registration No	: Listed in Annex IV / V REACH, exempted from registration.	
Chemical formula	: N2	
1.2. Relevant identified uses of the substand	ce or mixture and uses advised against	
Relevant identified uses	<ul> <li>Industrial and professional uses. Perform risk assessment prior to use.</li> <li>Fuel gas for welding, cutting, heating, brazing and soldering applications.</li> <li>Laser gas.</li> <li>Welding, cutting, heating and brazing.</li> </ul>	
Uses advised against	: None.	
1.3. Details of the supplier of the safety data	a sheet	
Air Liquide UK Ltd. Station Road Coleshill B46 1JY Birmingham United Kingdom <u>safety.aluk@airliquide.com</u>		
1.4. Emergency telephone number		
Emergency telephone number	: 01675 462695 (Available 24/7)	
SECTION 2: Hazards identification		
2.1. Classification of the substance or mixtu	ire	
Classification according to Regulation (EC)		
	ure : Compressed gas H280	
2.2. Label elements		
Labelling according to Regulation (EC) No. 1	1272/2008 ICLP1	
Hazard pictograms (CLP)	GHS04	
Signal word (CLP) Hazard statements (CLP)	: Warning : H280 - Contains gas under pressure; may explode if heated.	



**LASAL 2001** 

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01496

Precautionary statements (CLP) - Storage

: P403 - Store in a well-ventilated place.

#### 2.3. Other hazards

Asphyxiant in high concentrations.

The substance/mixture has no endocrine disrupting properties.

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Nitrogen	CAS-No.: 7727-37-9 EC-No.: 231-783-9 EC Index-No.: REACH registration No: *1	100	Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*3: Registration not required: Substance manufactured or imported < 1t/y. Not applicable

3.2. Mixtures

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

- Inhalation	<ul> <li>Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.</li> </ul>
- Skin contact	: Adverse effects not expected from this product.
- Eye contact	: Adverse effects not expected from this product.
- Ingestion	: Ingestion is not considered a potential route of exposure.
4.2. Most important symptoms and	l effects, both acute and delayed
	In high concentrations may cause asphyxiation. Symptoms may include loss of

# mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures			
5.1. Extinguishing media			
- Suitable extinguishing media	: Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire.		
- Unsuitable extinguishing media	: Do not use water jet to extinguish.		
5.2. Special hazards arising from the substance or mixture			
Specific hazards	: Exposure to fire may cause containers to rupture/explode.		
Hazardous combustion products	: None.		



LASAL 2001

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01496

5.3. Advice for firefighters	
Specific methods	<ul> <li>Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.</li> <li>If possible, stop flow of product.</li> <li>Use water spray or fog to knock down fire fumes if possible.</li> <li>Move containers away from the fire area if this can be done without risk.</li> </ul>
Special protective equipment for fire fighters	<ul> <li>In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.</li> <li>Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</li> <li>Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.</li> </ul>

### **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	: Act in accordance with local emergency plan.		
	Try to stop release.		
	Evacuate area.		
	Ensure adequate air ventilation.		
	Stay upwind.		
	See section 8 of the SDS for more information on personal protective equipment.		
For emergency responders	: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.		
	Oxygen detectors should be used when asphyxiating gases may be released.		
	See section 5.3 of the SDS for more information.		
6.2. Environmental precautions			
	Try to stop release.		
6.3. Methods and material for containment and cleaning up			
	Ventilate area.		
6.4. Reference to other sections			
	See also sections 8 and 13.		

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Safe use of the product	: Do not breathe gas.
	. Do not breathe gas.
	Avoid release of product into atmosphere.
	The product must be handled in accordance with good industrial hygiene and safety procedures.
	1
	Only experienced and properly instructed persons should handle gases under pressure.
	Consider pressure relief device(s) in gas installations.
	Ensure the complete gas system was (or is regularily) checked for leaks before use.
	Do not smoke while handling product.
	Use only properly specified equipment which is suitable for this product, its supply pressure
	and temperature. Contact your gas supplier if in doubt.
	Avoid suck back of water, acid and alkalis.



# LASAL 2001

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01496

Safe handling of the gas receptacle	: Refer to supplier's container handling instructions.
	Do not allow backfeed into the container.
	Protect containers from physical damage; do not drag, roll, slide or drop.
	When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.)
	designed to transport cylinders.
	Leave valve protection caps in place until the container has been secured against either a
	wall or bench or placed in a container stand and is ready for use.
	If user experiences any difficulty operating valve discontinue use and contact supplier.
	Never attempt to repair or modify container valves or safety relief devices.
	Damaged valves should be reported immediately to the supplier.
	Keep container valve outlets clean and free from contaminants particularly oil and water.
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another.
	Never use direct flame or electrical heating devices to raise the pressure of a container.
	Do not remove or deface labels provided by the supplier for the identification of the content of the container.
	Suck back of water into the container must be prevented.
	Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, including	any incompatibilities
	Observe all regulations and local requirements regarding storage of containers.
	Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place.
	Containers should be stored in the vertical position and properly secured to prevent them
	from falling over.
	Stored containers should be periodically checked for general condition and leakage.
	Keep container below 50°C in a well ventilated place.
	Store containers in location free from fire risk and away from sources of heat and ignition.
	Keep away from combustible materials.
7.3. Specific end use(s)	
	None

None.

8.1. Control parameters         OEL (Occupational Exposure Limits)       : None available.         DNEL (Derived-No Effect Level)       : None available.         PNEC (Predicted No-Effect Concentration)       : None available.         8.2. Exposure controls       : None available.         8.2.1. Appropriate engineering controls       : Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Oxygen detectors should be used when asphyxiating gases may be rele Consider the use of a work permit system e.g. for maintenance activities         8.2.2. Individual protection measures, e.g. personal protective equipment       A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matche The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be select         • Eye/face protection       : Wear safety glasses with side shields. Standard EN 166 - Personal eve-protection - specifications.	SECTION 8: Exposure controls/personal protection		
DNEL (Derived-No Effect Level)       : None available.         PNEC (Predicted No-Effect Concentration)       : None available.         8.2. Exposure controls       .         8.2.1. Appropriate engineering controls       Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Oxygen detectors should be used when asphyxiating gases may be rele Consider the use of a work permit system e.g. for maintenance activities         8.2.2. Individual protection measures, e.g. personal       protective equipment         A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matche The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be select         • Eye/face protection       : Wear safety glasses with side shields.			
PNEC (Predicted No-Effect Concentration)       : None available.         8.2. Exposure controls         8.2.1. Appropriate engineering controls         Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Oxygen detectors should be used when asphyxiating gases may be rele Consider the use of a work permit system e.g. for maintenance activities         8.2.2. Individual protection measures, e.g. personal protective equipment         A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matche The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be select         • Eye/face protection       : Wear safety glasses with side shields.			
8.2. Exposure controls         8.2.1. Appropriate engineering controls         Provide adequate general and local exhaust ventilation.         Systems under pressure should be regularily checked for leakages.         Oxygen detectors should be used when asphyxiating gases may be rele         Consider the use of a work permit system e.g. for maintenance activities         8.2.2. Individual protection measures, e.g. personal protective equipment         A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matched The following recommendations should be considered:         PPE compliant to the recommended EN/ISO standards should be select         • Eye/face protection       : Wear safety glasses with side shields.			
8.2.1. Appropriate engineering controls         Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Oxygen detectors should be used when asphyxiating gases may be rele Consider the use of a work permit system e.g. for maintenance activities         8.2.2. Individual protection measures, e.g. personal protective equipment         A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matche The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be select         • Eye/face protection       : Wear safety glasses with side shields.			
Provide adequate general and local exhaust ventilation.         Systems under pressure should be regularily checked for leakages.         Oxygen detectors should be used when asphyxiating gases may be rele         Consider the use of a work permit system e.g. for maintenance activities         8.2.2. Individual protection measures, e.g. personal protective equipment         A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matche The following recommendations should be considered:         PPE compliant to the recommended EN/ISO standards should be select         • Eye/face protection       : Wear safety glasses with side shields.			
Systems under pressure should be regularily checked for leakages. Oxygen detectors should be used when asphyxiating gases may be relected for leakages. Oxygen detectors should be used when asphyxiating gases may be relected for leakages.         8.2.2. Individual protection measures, e.g. personal protective equipment         A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matched The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be select         • Eye/face protection       : Wear safety glasses with side shields.			
Oxygen detectors should be used when asphyxiating gases may be relectors should be used when asphyxiating gases may be relectors a work permit system e.g. for maintenance activities         8.2.2. Individual protection measures, e.g. personal protective equipment         A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matche The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be select         • Eye/face protection       : Wear safety glasses with side shields.			
<ul> <li>Consider the use of a work permit system e.g. for maintenance activities</li> <li>8.2.2. Individual protection measures, e.g. personal protective equipment         <ul> <li>A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matche The following recommendations should be considered:             <ul></ul></li></ul></li></ul>			
8.2.2. Individual protection measures, e.g. personal protective equipment         A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matche The following recommendations should be considered:         • Eye/face protection       : Wear safety glasses with side shields.			
A risk assessment should be conducted and documented in each work a risks related to the use of the product and to select the PPE that matche The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be select Wear safety glasses with side shields.			
<ul> <li>risks related to the use of the product and to select the PPE that matche The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be select</li> <li>Eye/face protection : Wear safety glasses with side shields.</li> </ul>			
Eye/face protection     The following recommendations should be considered:     PPE compliant to the recommended EN/ISO standards should be select     Wear safety glasses with side shields.	irea to assess the		
• Eye/face protection     • Eye/face protection     • Eye/face protection     • Eye/face protection	s the relevant risk.		
• Eye/face protection : Wear safety glasses with side shields.			
	ed.		
Standard EN 166 - Personal eve-protection - specifications			
Skin protection			



## LASAL 2001

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01496

- Hand protection	: Wear working gloves when handling gas containers.
- Other	<ul> <li>Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.</li> <li>Wear safety shoes while handling containers.</li> <li>Standard EN ISO 20345 - Personal protective equipment - Safety footwear.</li> </ul>
Respiratory protection	<ul> <li>Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</li> </ul>
	Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.
	Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
Thermal hazards	: None in addition to the above sections.
8.2.3. Environmental exposure controls	
	None necessary.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas.
- Colour	: Colourless.
Odour	: No odour warning properties.
Melting point / Freezing point	: -210 °C
Boiling point	: -196 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available.
Upper explosion limit	: Not available.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
pH	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: No reliable data available.
Water solubility [20°C]	: 20 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not available.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable.
Relative vapour density (air=1)	: 0.97
Particle characteristics	: Not applicable for gases and gas mixtures.

### 9.2. Other information

9.2.1. Information with regard to physical hazard classes			
Explosion limits	:	Non flammable.	
Oxidising properties	:	No oxidising properties.	
Critical temperature [°C]	:	-147 °C	
9.2.2. Other safety characteristics			
Molar mass	:	28 g/mol	
Other data	:	None.	

# SECTION 10: Stability and reactivity

### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

#### 10.2. Chemical stability

Stable under normal conditions.



LASAL 2001

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01496

10.3. Possibility of hazardous reactions	
	None.
10.4. Conditions to avoid	
	Avoid moisture in installation systems.
10.5. Incompatible materials	
	For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	None.

# SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008	
Acute toxicity	: No known toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
11.2. Information on other hazards	
Other information	: The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological informat	ion
12.1. Toxicity	
Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No ecological damage caused by this product.
<u>12.4. Mobility in soil</u>	
Assessment	: No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessme	<u>nt</u>
Assessment	: Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
Assessment	: The substance/mixture has no endocrine disrupting properties.
12.7. Other adverse effects	
Other adverse effects	: No known effects from this product.



LASAL 2001

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01496

Effect on the ozone layer Effect on global war

- : No effect on the ozone layer.
- NI.

Effect on global warming	: None.
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
	May be vented to atmosphere in a well ventilated place.
	Do not discharge into any place where its accumulation could be dangerous.
List of hazardous waste codes (from Commission	Return unused product in original container to supplier. : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.
Decision 2000/532/EC as amended)	
13.2. Additional information	
	External treatment and disposal of waste should comply with applicable local and/or national regulations.
SECTION 14: Transport information	
14.1. UN number or ID number	
In accordance with ADR / RID / IMDG / IATA / ADN UN-No.	: 1066
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	: NITROGEN, COMPRESSED
Transport by air (ICAO-TI / IATA-DGR)	: Nitrogen, compressed
Transport by sea (IMDG)	: NITROGEN, COMPRESSED
14.3. Transport hazard class(es)	
Labelling	: 2.2 : Non-flammable, non-toxic gases.
Transport by road/rail (ADR/RID)	
Class	: 2
Classification code	: 1A
Hazard identification number	: 20
Tunnel Restriction	: E - Passage forbidden through tunnels of category E

### Transport by air (ICAO-TI / IATA-DGR) Class / Div. (Sub. risk(s))

### Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) Emergency Schedule (EmS) - Fire Emergency Schedule (EmS) - Spillage

#### 14.4. Packing group

Transport by road/rail (ADR/RID)
Transport by air (ICAO-TI / IATA-DGR)
Transport by sea (IMDG)

## 14.5. Environmental hazards

Transport by road/rail (ADR/RID)
Transport by air (ICAO-TI / IATA-DGR)
Transport by sea (IMDG)

: 2.2 : F-C : S-V

: 2.2

- : Not applicable.
- : Not applicable.
- : Not applicable.
- : None.
- : None.
- : None.



: P200.

: 200.

: 200.

: P200.

### LASAL 2001

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01496

#### 14.6. Special precautions for user

#### Packing Instruction(s)

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft Cargo Aircraft only Transport by sea (IMDG)

Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

- Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **SECTION 15: Regulatory information**

,	
EU-Regulations	
Restrictions on use Other information, restriction and prohibition regulations Seveso Directive : 2012/18/EU (Seveso III)	<ul> <li>None.</li> <li>LASAL 2001 is not subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 july 2012 concerning the export and import of hazardous chemicals.</li> <li>Not covered.</li> </ul>
National regulations	
Water hazard class (WGK) Kenn-Nr. Regulatory reference	: nwg - Non-hazardous to water. : 1351 : Ensure all national/local regulations are observed.
15.2. Chemical safety assessment	
	A CSA does not need to be carried out for this product.

#### **SECTION 16: Other information**

Indication of changes

: Safety data sheet in accordance with commission regulation (EU) No 2020/878.



LASAL 2001

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01496

Abbreviations and acronyms	<ul> <li>ATE - Acute Toxicity Estimate.</li> <li>CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.</li> <li>REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.</li> <li>EINECS - European Inventory of Existing Commercial Chemical Substances.</li> <li>CAS# - Chemical Abstract Service number.</li> <li>PPE - Personal Protection Equipment.</li> <li>LC50 - Lethal Concentration to 50 % of a test population.</li> <li>RMM - Risk Management Measures.</li> <li>PBT - Persistent, Bioaccumulative and Toxic.</li> <li>vPvB - Very Persistent and Very Bioaccumulative.</li> <li>STOT - SE : Specific Target Organ Toxicity - Single Exposure.</li> <li>CSA - Chemical Safety Assessment.</li> <li>EN - European Standard.</li> <li>UN - United Nations.</li> <li>ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road.</li> <li>IATA - International Air Transport Association.</li> <li>IMDG code - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Road.</li> <li>IXTA - International Maritime Dangerous Goods.</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Road.</li> <li>IVT - Water Hazard Class.</li> <li>STOT - RE : Specific Target Organ Toxicity - Repeated Exposure.</li> <li>UFI : Unique Formula Identifier.</li> </ul>
Training advice	<ul> <li>The hazard of asphyxiation is often overlooked and must be stressed during operator training.</li> <li>For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu</li> </ul>
Further information	<ul> <li>Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).</li> <li>Key literature references and sources of data are maintained in EIGA doc 169 :</li> <li>'Classification and Labelling Guide', downloadable at http://www.Eiga.eu .</li> </ul>

Full text of H- and EUH-statements	
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
DISCLAIMER OF LIABILITY	: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

or damage resulting from its use can be accepted.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury

End of document