

≤15% Carbon dioxide, ≤20% Oxygen in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512 Issue date: 1/4/2024 Version: 1.0

Warning



SECTION 1: Identific	ation of the substance/mixture and of the company/undertaking
1.1. Product identifier	
SDS no	: SDS 01512
1.2. Relevant identified us	ses of the substance or mixture and uses advised against
Relevant identified uses Uses advised against	 Industrial and professional use for chemical analysis, calibration, (routine) quality control, laboratory use, under controlled conditions. Consumer use.
	Uses other than those listed above are not supported, contact your supplier for more information on other uses.
1.3. Details of the supplier	r of the safety data sheet
Air Liquide UK Ltd. Station Road Coleshill	
B46 1JY Birmingham United Kingdom safety.aluk@airliquide.com	
1.4. Emergency telephone	a number
Emergency telephone numb	ber : 01675 462695 (Available 24/7)
SECTION 2: Hazards	identification
2.1. Classification of the s	substance or mixture
Classification according to	o Regulation (EC) No. 1272/2008 [CLP]
Physical hazards	Gases under pressure : Compressed gas H280
2.2. Label elements	
Labelling according to Reg	gulation (EC) No. 1272/2008 [CLP]
Hazard pictograms (CLP)	GHS04
Signal word (CLP)	: Warning
Hazard statements (CLP) Precautionary statements (C	: H280 - Contains gas under pressure; may explode if heated.
- Storage	: P403 - Store in a well-ventilated place.
2.3. Other hazards	
	Not classified as PBT or vPvB.
	The substance/mixture has no endocrine disrupting properties.



≤15% Carbon dioxide, ≤20% Oxygen in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Nitrogen	CAS-No.: 7727-37-9 EC-No.: 231-783-9 EC Index-No.: REACH-no: *1	65	Press. Gas (Comp.), H280
Oxygen	CAS-No.: 7782-44-7 EC-No.: 231-956-9 EC Index-No.: 008-001-00-8 REACH-no: *1	≤ 20	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Carbon dioxide	CAS-No.: 124-38-9 EC-No.: 204-696-9 EC Index-No.: REACH-no: *1	≤ 15	Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures		
4.1. Description of first aid mea	sures	
- Inhalation	: Adverse effects not expected from this product.	
- Skin contact	: Adverse effects not expected from this product.	
- Eye contact	: Adverse effects not expected from this product.	
- Ingestion	: Ingestion is not considered a potential route of exposure.	
4.2. Most important symptoms and effects, both acute and delayed		
	See section 11.	
4.3. Indication of any immediate medical attention and special treatment needed		

None.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
- Suitable extinguishing media	: Water spray or fog.	
- Unsuitable extinguishing media	Product does not burn, use fire control measures appropriate for the surrounding fire. Do not use water jet to extinguish.	
5.2. Special hazards arising from the substance or mixture		
Specific hazards	: Supports combustion.	
Hazardous combustion products	Exposure to fire may cause containers to rupture/explode. : None.	



for firefighters.

≤15% Carbon dioxide, ≤20% Oxygen in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512

5.3. Advice for firefighters	
Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering
	sewers and drainage systems.
	If possible, stop flow of product.
	Use water spray or fog to knock down fire fumes if possible.
	Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	: Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
	Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
	Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	 Act in accordance with local emergency plan. Stay upwind. See section 8 of the SDS for more information on personal protective equipment. 	
For emergency responders	: See section 5.3 of the SDS for more information.	
6.2. Environmental precautions		
	None.	
6.3. Methods and material for containment and cleaning up		
	None.	
6.4. Reference to other sections		
	See also sections 8 and 13.	
SECTION 7: Handling and storage		

7.1. Precautions for safe handling

Safe use of the product	: Do not breathe gas.
	Avoid release of product into atmosphere.
	The product must be handled in accordance with good industrial hygiene and safety
	procedures.
	Only experienced and properly instructed persons should handle gases under pressure.
	Consider pressure relief device(s) in gas installations.
	Ensure the complete gas system was (or is regularily) checked for leaks before use.
	Do not smoke while handling product.
	Use only properly specified equipment which is suitable for this product, its supply pressure
	and temperature. Contact your gas supplier if in doubt.
	Use only oxygen approved lubricants and oxygen approved sealings.
	Avoid suck back of water, acid and alkalis.



≤15% Carbon dioxide, ≤20% Oxygen in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512

Safe handling of the gas receptacle	 Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, including any inc	compatibilities
	Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.
7.3. Specific end use(s)	None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon dioxide (124-38-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Carbon dioxide
IOEL TWA	9000 mg/m³
	5000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC

DNEL (Derived-No Effect Level)

: None available.

: None available.

PNEC (Predicted No-Effect Concentration)



≤15% Carbon dioxide, ≤20% Oxygen in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512

8.2. Exposure controls

8.2.1. Appropriate engineering controls		
	Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Consider the use of a work permit system e.g. for maintenance activities.	
8.2.2. Individual protection measures, e.g. personal protective equipment		
	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.	
• Eye/face protection	: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications.	
Skin protection		
- Hand protection	: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher.	
- Other	: Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.	
Respiratory protection	 Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. When indicated by a risk assessment, Respiratory Protective Equipment must be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems. 	
Thermal hazards	: None in addition to the above sections.	
8.2.3. Environmental exposure controls		

None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas.
- Colour	: Colourless.
Odour	: Odourless.
Melting point / Freezing point	: Not applicable for gases and gas mixtures.
Boiling point	: Not applicable for gas mixtures.
	It is technically not possible to determine the boiling point or range of this mixture.
	Component with lowest boiling point: Nitrogen -196 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
рН	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: Not applicable for gases and gas mixtures.
Water solubility [20°C]	: Mixture is partially soluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable.
Relative vapour density (air=1)	: Lighter or similar to air.



≤15% Carbon dioxide, ≤20% Oxygen in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512

Particle characteristics	: Not applicable for gases and gas mixtures.
9.2. Other information	
9.2.1. Information with regard to physical hazard	classes
Explosion limits	: Non flammable.
Oxidising properties	: No oxidising properties.
9.2.2. Other safety characteristics	
Other data	: None.
SECTION 10: Stability and reactivity	
10.1. Reactivity	
	Data for mixtures are not available. This mixture contains components with the following reactivity: Violently oxidises organic material.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	None.
10.4. Conditions to avoid	
	Avoid moisture in installation systems.
10.5. Incompatible materials	
	For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	: Toxicological effects not expected from this product if occupational exposure limit values are not exceeded.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.



 \leq 15% Carbon dioxide, \leq 20% Oxygen in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512

Aspiration hazard	: Not applicable for gases and gas mixtures.
11.2. Information on other hazards	
Other information	 For more information, see 'EIGA Safety Info 24: Carbon Dioxide, Physiological Hazards' at www.eiga.eu. Unlike simple asphyxiants, carbon dioxide has the ability to cause death even when normal oxygen levels (20-21%) are maintained. 5% CO2 has been found to act synergistically to increase the toxicity of certain other gases (CO, NO2). CO2 has been shown to enhance the production of carboxy- or met-hemoglobin by these gases possibly due to carbon dioxide's stimulatory effects on the respiratory and circulatory systems. The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.

Carbon dioxide (124-38-9)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

Oxygen (7782-44-7)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.

Nitrogen (7727-37-9)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No ecological damage caused by this product.
<u>12.4. Mobility in soil</u>	
Assessment	: No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
Assessment	: The substance/mixture has no endocrine disrupting properties.



≤15% Carbon dioxide, ≤20% Oxygen in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512

12.7. Other adverse effects

Other adverse effects Effect on the ozone layer Effect on global warming

- : No known effects from this product.
 - : No effect on the ozone layer.
 - : Contains greenhouse gas(es).

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
	May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous.
	Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information	
	External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number	
In accordance with ADR / RID / IMDG / IATA / ADN UN-No.	: 1956
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	: COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen)
Transport by air (ICAO-TI / IATA-DGR)	: Compressed gas, n.o.s. (Nitrogen, Oxygen)
Transport by sea (IMDG)	: COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen)
14.3. Transport hazard class(es)	
Labelling	
	2.2 : Non-flammable, non-toxic gases.
Transport by road/rail (ADR/RID)	
Class Classification code	: 2
Classification code Hazard identification number	: 1A : 20
Tunnel Restriction	E - Passage forbidden through tunnels of category E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.2
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.2
Emergency Schedule (EmS) - Fire	: F-C
Emergency Schedule (EmS) - Spillage	: S-V
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable.
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable.
Transport by sea (IMDG)	: Not applicable.
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Air Linuida LUZ Ltd	



≤15% Carbon dioxide, ≤20% Oxygen in

Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512

Transport by sea (IMDG)	: None.
14.6. Special precautions for user	
Packing Instruction(s)	
Transport by road/rail (ADR/RID)	: P200.
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: 200.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200.
Special transport precautions	 Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in
	the event of an accident or an emergency.
	Before transporting product containers:
	- Ensure there is adequate ventilation.
	- Ensure that containers are firmly secured.
	- Ensure valve is closed and not leaking.
	 Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
	- Ensure valve protection device (where provided) is correctly fitted.
14.7. Maritime transport in bulk according	to IMO instruments
	Not applicable.
SECTION 15: Regulatory informat	ion

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

substance on the REACH candidate list. Substance subject to Regulation (EU) No 649/2012 of the European Parliament uncil of 4 July 2012 concerning the export and import of hazardous chemicals.
ional/local regulations are observed.
not need to be carried out for this product.
s

SECTION 16: Other information	
-------------------------------	--

Indication of changes

: Safety data sheet in accordance with commission regulation (EU) No 2020/878.



≤15% Carbon dioxide, ≤20% Oxygen in Nitrogen

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: SDS 01512

Abbreviations and acronyms	: ATE - Acute Toxicity Estimate.
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.
	REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
	EINECS - European Inventory of Existing Commercial Chemical Substances.
	CAS# - Chemical Abstract Service number.
	PPE - Personal Protection Equipment.
	LC50 - Lethal Concentration to 50 % of a test population.
	RMM - Risk Management Measures.
	PBT - Persistent, Bioaccumulative and Toxic.
	vPvB - Very Persistent and Very Bioaccumulative.
	STOT- SE : Specific Target Organ Toxicity - Single Exposure.
	CSA - Chemical Safety Assessment.
	EN - European Standard.
	UN - United Nations.
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by
	Road.
	IATA - International Air Transport Association.
	IMDG code - International Maritime Dangerous Goods.
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail. WGK - Water Hazard Class.
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure.
	UFI : Unique Formula Identifier.
Training advice	: None.
Further information	 Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : http://www.eiga.eu.
	Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).

Full text of H- and EUH-statements	
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

DISCLAIMER OF LIABILITY

 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document